

GAS TANK-TYPE WATER HEATERS

Reliability and Efficiency For Light-Duty Applications



Conservationist® Models Provide Thermal Efficiency of 78% to 80%



Conservationist® models provide reliable, efficient service for light-duty applications such as office buildings and duplex/fourplex apartment homes.

Quality Features:

ALL MODELS

- **CoreGard™ Anode Rod** – Stainless steel core won't corrode, won't break away.
- **Three-year limited tank warranty**
- **Handhole cleanout** – For easy maintenance.
- **All models meet ASHRAE/IES 90.1b-1992 requirements**
- **Fully-automatic controls** – Includes automatic safety shutoff gas if pilot is extinguished and high-temperature energy cutoff (ECO).
- **PermaGlas® glass lining** – Prevents tank corrosion and provides years of clean, hot water.
- **Factory-installed T & P valve** – Properly sized for each model.
- **Compact design** – Smaller diameters and shorter heights for greater installation flexibility.

All Dimensions in Inches

Model Number	Gal. Cap.	Type of Gas	BTU Input Per Hour	Recovery Cap. Temp Rise Degrees F-GPM			Vent Size	Height	Diameter	Ship Weight (lbs.)
				40	100	140				
BT-65	60	nat/prop	60,000	131	48	35	4	64-3/4	20-1/4	165
BT-80	75	nat/prop	75,100	157	65	45	4	81-1/8	25-1/2	291
BT-100	100	nat/prop	75,100	157	65	45	4	88-3/4	26-1/2	308



ASME